

SEE DTM 6041-002 FOR DIVERSION ROUTE DETAIL

Moor Lane closed ahead At Highmoor Road For Siviter's Lane follow diversion

KEY

- Cone
- Sign
- Work area
- Diversion route

DETAIL B



Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) 45 degree tapers have 1.5m spacing and no relaxations.
- 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2



Single carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Min width of sideways safety zone (S)	0.5 m
Min length of longways clearance (L)	0.5 m
Speed of the road	30

Rev	Description	By	Chk	Date
Revisions				

Client:
nationalgrid

Project:
Moor Lane,
Rowley Regis, B65 8DL
Grid Ref: (x)396849 ; (y)286983

Title:
Road Closure And Diversion



Design: ACW	Drawn: ACW	Chkd: OP
Date: 12/11/24	Date: 12/11/24	Date: 12/11/24
Scale: A3 - NTS	Status: Proposed	
Drawing No	Rev:	
DTM6041 - 001	-	

NOTE
Access & Egress For
Emergency Services And
Residents To Be Managed On
Site

SEE DTM 6041-002 FOR DIVERSION ROUTE DETAIL

